

ITEM / SKU

OCVB400B.....	4 Rolls Per Box, 400ft ² (37.2m ²)
OCVB7200P.....	72 Rolls Per Palletized Box, 7,200ft ² (668.9m ²)

PRODUCT DIMENSIONS

Roll Size	3' x 33'4" Roll, 100ft ² (0.9m x 10.2m Roll, 9.3m ²)
Roll Weight.....	13lbs (5.9kg)
4 Roll Box Dimensions	37.5"H x 12"W x 12"L (1m x 0.3m x 0.3m)
4 Roll Box Weight	53lbs (24kg)
72 Roll Palletized Box Dimensions	49"H x 48"W x 40"L (1.2m x 122m x 1m)
72 Roll Palletized Box Weight	980lbs (444.5kg)

PRODUCT SPECIFICATIONS*

Material Composition	Frothed Polyurethane Foam with Polyethylene Vapor Barrier
Thickness (ASTM D3574)	0.055" (1.4mm)
Density (ASTM D3574)	25lbs/ft ³ (400.5kg/m ³)
Compression Set (ASTM D3574)	5% max
Tensile Strength (ASTM D3574)	100lbs/ft ² (488.2kg/m ²)
Indentation Load Deflection - 25% (ASTM D3574)	32lbs/ft ² (156.2kg/m ²)
Indentation Load Deflection - 65% (ASTM D3574)	200+lbs/ft ² (976.5+kg/m ²)
NBS Smoke Density (ASTM E662)	<100 max
Flammability Test (DOC FF 1-70).....	Pass
Thermal Transmission R-Value (ASTM C518)	0.08 °F ft ² h/Btu (Excellent for Radiant Heated Floors)
Water Vapor Transmission (ASTM E96)	0.46 grains/h•ft ²
Antimicrobial Protection	Ultra-Fresh® Antimicrobial Protection
Indoor Air Quality.....	UL GREENGUARD® GOLD Certified for Low Chemical Emissions - UL2818
Installation Method	Approved for Floating and Nail-Down Installation
Warranty	Warranted for Equal Term to that of the Primary Floor Covering
Moisture & Vapor Warranty (ASTM F1869).....	Warranted up to 10lbs / 1,000ft ² / 24hrs of Vapor Emissions

*Specifications are Subject to ±10% Manufacturing Tolerance.

SOUND RATING*

Laminate & Wood Floors (ASTM E492).....	71 IIC
Laminate & Wood Floors (ASTM E413).....	67 STC
Luxury Vinyl Tile (LVT) (ASTM E492)	73 IIC
Luxury Vinyl Tile (LVT) (ASTM E413)	67 STC

*The Results of the Impact Insulation Class (IIC) and Sound Transmission Class (STC) are Influenced by the Complete Floor-Ceiling Construction.

SUSTAINABILITY & RECYCLABILITY

Renewable & Natural Content	>50% (Made in Part with Soybean Oil and Other Natural Non-Petrochemical Resources)
Recyclability	100% Post-Consumer Recyclable
LEED Credit IEQ 4.3	Low-Emitting Materials-Flooring Systems
LEED Credit MR 6.0	Rapidly Renewable Materials
LEED Credit MR 5.1	10% Extracted, Processed & Manufactured Regionally
LEED Credit MR 5.2	20% Extracted, Processed & Manufactured Regionally

