

4 ROLL JOB PACK (SKU: OC400B)

Box Quantity	4 Rolls Per Box, 400ft ² (37.2m ²)
Roll Size	3' x 33'4" Roll, 100ft ² (0.9m x 10.2m Roll, 9.3m ²)
Roll Weight	12lbs (5.4kg)
4 Roll Box Dimensions	37.5"H x 12"W x 12"L (1m x 0.3m x 0.3m)
4 Roll Box Weight	49lbs (22.2kg)




72 ROLL DISTRIBUTOR PALLET (SKU: OC72009)

Palletized Box Quantity	72 Rolls Per Palletized Box, 7,200ft ² (668.9m ²)
Roll Size	3' x 33'4" Roll, 100ft ² (0.9m x 10.2m Roll, 9.3m ²)
Roll Weight	12lbs (5.4kg)
Palletized Box Dimensions	49"H x 48"W x 40"L (1.2m x 122m x 1m)
Palletized Box Weight	910lbs (412.8kg)



MASTER ROLL (SKU: OC3600R)

Roll Dimensions	6' X 600', 3,600ft ² (334.5m ²)
Roll Weight	432lbs (196kg)



PRODUCT SPECIFICATIONS†

Material Composition	Frothed Polyurethane Foam
Thickness (ASTM D3574)	0.055" (1.4mm)
Density (ASTM D3574)	25lbs/ft ³ (400.5kg/m ³)
Compression Set (ASTM D3574)	5% max
Tensile Strength (ASTM D3574)	100lbs/ft ² (488.2kg/m ²)
Indentation Load Deflection - 25% (ASTM D3574)	32lbs/ft ² (156.2kg/m ²)
Indentation Load Deflection - 65% (ASTM D3574)	200+lbs/ft ² (976.5+kg/m ²)
NBS Smoke Density (ASTM E662)	<100 max
Flammability Test (DOC FF 1-70)	Pass
Thermal Transmission R-Value (ASTM C518)	0.08 °F ft ² h/Btu (Excellent for Radiant Heated Floors)
Water Vapor Transmission	For Installations Requiring Moisture Protection Use OmniChoice Vapor Bloc
Antimicrobial Protection	Ultra-Fresh® Antimicrobial Protection
Indoor Air Quality	UL GREENGUARD® GOLD Certified for Low Chemical Emissions - UL2818
Installation Method	Approved for Floating, Nail-Down, Glue-Down, and Thin-Set Installation
Warranty	Warranted for Equal Term to that of the Primary Floor Covering

SOUND RATING††

Laminate & Wood Floors (ASTM E492)	71 IIC
Laminate & Wood Floors (ASTM E413)	67 STC
Luxury Vinyl Tile (LVT) (ASTM E492)	73 IIC
Luxury Vinyl Tile (LVT) (ASTM E413)	67 STC
Ceramic Tile (ASTM E492)	51 IIC
Ceramic Tile (ASTM E413)	54 STC

SUSTAINABILITY & RECYCLABILITY

Renewable & Natural Content	>50% (Made in Part with Soybean Oil and Other Natural Non-Petrochemical Resources)
Recyclability	100% Post-Consumer Recyclable
LEED Credit IEQ 4.3	Low-Emitting Materials-Flooring Systems
LEED Credit MR 6.0	Rapidly Renewable Materials
LEED Credit MR 5.1	10% Extracted, Processed & Manufactured Regionally
LEED Credit MR 5.2	20% Extracted, Processed & Manufactured Regionally

†Specifications are Subject to ±10% Manufacturing Tolerance.

††The Results of the Impact Insulation Class (IIC) and Sound Transmission Class (STC) are Influenced by the Complete Floor-Ceiling Construction.