


- **Dampens sound** and room noise in today's active environments
- Guardian™ antimicrobial inhibits the growth of mold, mildew, and odor-causing bacteria
- Smooths out minor floor irregularities
- Installs quickly and easily
- For use over in-floor heating and is recommended by the RPA as an excellent choice
- Hypoallergenic and CRI Green Label Plus-certified

- For use under
- **Luxury vinyl tile/plank**
 - **Rigid composite**
 - **Other premium resilient flooring**
 - Laminate
 - Engineered wood
 - Solid Hardwood

SPECIFICATIONS

Product Code:	BV0340
Composition:	Made of High-Density Synthetic Rubber
Density:	62 lbs/ft ³ or 42 oz/yd ²
Thickness:	0.056" (1.42 mm)
R-Value:	0.02
Moisture Barrier:	N/A*
Color:	Red
Castor Durability Test:	Passes 25,000 Cycles**
Dimension:	54" x 44.44'
Ft ² /Roll:	200
Yd ² /Roll:	22.22
Roll Weight:	58 lbs.



ACOUSTICAL PROPERTIES

Impact Insulation Class (IIC)***	66
ΔIIC	22
Sound Transmission Class (STC)***	63

PROTECTION

Indoor Air Quality:	CRI Green Label Plus-Certified
Antimicrobial:	Yes
Warranty:	Limited

*Separate moisture barrier should be used on slab foundation and below-grade installation

**Passes Castor Durability Test for 25,000 cycles when tested under minimum of 3 mm double-glued luxury vinyl plank and minimum 3.2 mm floating-click

***When tested with floor – ceiling assembly

IIC: ASTM E492-09/ASTM E989-06
 ΔIIC: AaASTM E2179-03
 STC: ASTM E90/ASTM E413-10

