

NORTHWINDS

LUXURY VINYL PLANK



CLICK

SPECIFICATIONS

PHYSICAL CONSTRUCTION

COMPOSITION:	Stabilicor™ (Polymeric/Extruded Composite Core)
CONSTRUCTION:	Click Lock
WEAR LAYER THICKNESS:	22 Mil
OVERALL THICKNESS:	7.5mm (6.5mm + 1mm Cork Back)
BACKING:	Natural Cork
FINISH:	UV Polyurethane
EDGE PROFILE:	Painted Bevel
ANTIMICROBIAL TREATMENT:	Yes
INSTALLATION:	Floating/Intermediate Level
LOCKING SYSTEM:	Longside-Valage, Shortside-Drop
RECOMMENDED ADHESIVE:	None Required
MEASUREMENTS:	9"x60" 8 planks per carton/30 sq ft per carton 48 cartons per pallet/1,440 sq ft per pallet
WARRANTY:	Lifetime Limited Residential Wear
ADDITIONAL BENEFITS:	100% Waterproof, Floor Score Certified, Antimicrobial, Scratch & Slip-Resistant



Stabilicor™




CERTIFIED BY
SCS Global Services

COLORWAYS



LAVA OAK - HF840
HIGH SHADE VARIATION



SEASIDE OAK - HF841



SMOKED OAK - HF842



ANTIQUÉ OAK - HF843

NOTE: Specifications are subject to normal manufacturing variances. Specifications are subject to change without notice when technological advancements provide improved product performance.